the Ort of optics

**O**ng**e**nieux°

APRIL 2014 COLLECTION





Today we continue to develop innovative products that fulfill our customers' needs for optics that will deliver superior performance well into the future.
















## The art of innovation

Our unwavering drive to envision and produce superior zoom lenses has been widely recognized by the most prestigious organizations in the world. In September 2005 Angénieux received an Emmy Award® "for lens technology developments for solid state imagers for cameras in high definition formats" from the National Academy of Television Arts and Sciences. In February 2009, The Academy of Motion Picture Arts and Sciences presented Angénieux with a Scientific and Engineering Award® "for the optical and mechanical designs of the compact and lightweight Optimo 15-40mm and 28-76mm zoom lenses for handheld motion picture photography." We also received the 2012 Technical Achievement Award in February 2012 from the Society of Camera Operators for the design of the Optimo 15-40mm, 28-76mm and 45-120mm hand-held zoom lenses. And in September 2012 we were acknowledged with a CINEC Award for outstanding innovation in optics for our Optimo 45-120mm zoom lens.









# The art of manufacturing

We believe that commitment to precision in all areas of manufacturing makes it possible for you to realize your creative vision without compromise. That is why we practice the strictest quality control measures at every point in the production process. Certified ISO 9001 since 1990, Angénieux further demonstrated our concern for environmentally mindful practices through compliance with ISO 14001 in 2010. This overall dedication to excellence was acknowledged in 2013 when Angénieux was designated a living heritage company under the French government's Entreprise du Patrimoine Vivant program, recognizing companies with a living legacy and tradition of merit and innovation.





# Capturing the art of film around the world

Whether used on digital cinematography cameras, 35mm film cameras, or HD cameras, for documentaries, blockbuster movies or any of today's cutting edge productions, Angénieux Optimo lenses can be found on production sets around the world, every day. That's because prominent and budding cinematographers alike recognize the unmistakable performance, unique characteristics and the famous Angénieux "touch" that only Angénieux Optimo lenses deliver.











# Optimo long lenses for 35mm film and digital production

Setting the standard for optics technology and performance, the Optimo family of long lenses offers a range of zoom lenses to meet the most uncompromising requirements. Manufactured with exquisite precision, they help you bring greater artistry and cinematic expression to your shoot in any format. Optimo long lenses are now the reference lenses in every type of production from feature films, commercials, TV series and video clips to major sports events and concerts.







Extender 1.4x & Extender 2x

### Optimo 19.5 - 94 Long Lenses »Extremely fast aperture of T2.6 Zoom Ratio: 4.7X Focal Length: 19.5 - 94 mm »329° focus rotation with over 50 precise focus witness marks and minimal breathing Aperture: f/2.4 - T2.6MOD: 2 ft - 0.5 in - 0.62 m » Unrivaled optical performance rivaling prime **Internal Focus:** Yes lenses at equivalent focal lengths S35+: 31.4 mm diagonal Image Coverage: » Available in PL mount. PV mount available on request » Calibrated focus marks available in feet or 12.3 lbs - 5.6 kg Weight (approx.): meters 335 mm (PL) Length: 330 mm (Panavision) » Very robust and designed for easy maintenance Front Diameter: 136 mm

Field of view for 35 mm Academic (22x16 mm)

» Expanded capabilities with Optimo 2x or

1.4x range extenders

Focal Length:	19.5 mm	94 mm	
Horizontal angular field of view:	58.2°	13.4°	
Object dimensions at MOD (mm):	344x246	73x54	





Extender 1.4x & Extender 2x (with or without iris ring)



DSLR Mounts

### Optimo 24 - 290 Long Lenses Zoom Ratio: 12X »The reference lens of the industry Focal Length: 24 - 290 mm » Extremely fast aperture of T2.8 with no ramping f/2.5 - T2.8Aperture: MOD: 4 ft - 1.22 m »327° focus rotation with now over 70 precise Internal Focus: Yes focus witness marks and minimal breathing Image Coverage: 35 mm academic – 30 mm diagonal » Unrivaled optical performance across the entire with extenders, image coverage range rivaling prime lenses at equivalent focal becomes S35+: 31.4 mm diagonal lengths » Available in PL mount. Panavision mount conversion available at partner companies. Weight (approx.): 24.2 lbs - 11 kg Canon mount available upon request Length: 440 mm » Calibrated focus marks available in feet or meters

Front Diameter: 162 mm

Field of view for 35 mm Academic (22x16 mm)

» Expanded capabilities with Optimo 2x and 1.4x

range extenders

Focal Length:	24 mm	290 mm
Horizontal angular field of view:	49.2°	4.2°
Object dimensions at MOD (mm):	799x571	67x49





Extender 1.4x & Extender 2x

### Long Lenses Optimo 28 - 340 Zoom Ratio: 12X »The reference lens of the industry with Focal Length: 28 - 340 mm additional reach on tele side and larger image f/2.9 - T3.2Aperture: coverage MOD: 4 ft - 0.5 in - 1.23 m » Extremely fast aperture of T3.2 Internal Focus: Yes »327° focus rotation with over 70 precise focus witness marks and minimal breathing Image Coverage: S35+: 31.4 mm diagonal » Unrivaled optical performance rivaling prime lenses at equivalent focal lengths » Available in PL mount. PV mount available Weight (approx.): 24.4 lbs - 11.1 kg on request Length: 454 mm (PL) » Calibrated focus marks available in feet or

449 mm (Panavision)

Front Diameter: 162 mm

» Expanded capabilities with Optimo 2x and 1.4x range extenders

meters

### Field of view for 35 mm Academic (22x16 mm)

Focal Length:	28 mm	340 mm
Horizontal angular field of view:	42.7°	3.8°
Object dimensions at MOD (mm):	687x493	58x42



# Optimo lightweight lenses for 35mm film and digital production

Our suite of Optimo lightweight hand-held zoom lenses – including 15-40mm, 28-76mm and 45-120mm – lets you pack light without sacrificing performance. They deliver the extremely fast apertures with outstanding contrast and color reproduction that have made Optimo the choice for high-end productions by DPs all over the world. Take our family of Optimo zoom lenses on your next shoot and experience the difference.






### 15-40 Optimo Lightweight Lens + Optional Angénieux Servo Unit (ASU)



Angénieux Servo Unit provides control of zoom, focus and iris Optimo 15-40 Lens + ASU =  $2.62\ kg\ /\ 5.7\ lbs$ 



Compatible with broadcast remote handles and cinema remote control



Extender 1.4x & Extender 2x



DSLR Mounts



Wide Angle 0.75X

### Optimo 15 - 40 Lightweight Series » Renowned Optimo quality in a lightweight lens Zoom Ratio: 2.7X Focal Length: 15 - 40 mm » Extremely fast aperture of T2.6 with f/2.4 - T2.6Aperture: no ramping MOD: 2 ft - 0.6 m»320° focus rotation with over 50 precise focus Internal Focus: Yes witness marks and no breathing Image Coverage: S35+: 31.4 mm diagonal » Unrivaled optical performance rivaling prime lenses at equivalent focal lengths

**Weight (approx.):** 4.2 lbs – 1.92 kg

**Length:** 186 mm **Front Diameter:** 114 mm

» Expanded capabilities with Optimo 2x and 1.4x range extenders

» Available with PL mount. PV, Nikon and Canon

mounts available upon request

feet or meters

» Calibrated focus marks available in

### Field of view for 35 mm Academic (22x16 mm)


Focal Length:	15 mm	40 mm
Horizontal angular field of view:	73°	31.2°
Object dimensions at MOD (mm):	611x437	230x169



### Optimo Lightweight Lens + Optional Angénieux Servo Unit (ASU)



Angénieux Servo Unit provides control of zoom, focus and iris Optimo Lens + ASU = 2.62 kg / 5.7 lbs



Compatible with broadcast remote handles and cinema remote control



Extender 1.4x & Extender 2x



DSLR Mounts

### Optimo 28 - 76 Lightweight Series » Renowned Optimo quality in a lightweight Zoom Ratio: 2.7X lens Focal Length: 28 - 76 mm f/2.4 - T2.6Aperture: » Extremely fast aperture of T2.6 with 2 ft - 0.6 mno ramping MOD: **Internal Focus:** Yes »320° focus rotation with over 50 precise focus witness marks and no breathing Image Coverage: S35+: 31.4 mm diagonal

Weight (approx.): 4.2 lbs - 1.92 kg

**Length:** 186 mm **Front Diameter:** 114 mm

- » Unrivaled optical performance rivaling prime lenses at equivalent focal lengths
- » Available with PL mount. PV, Nikon and Canon mounts available upon request
- » Calibrated focus marks available in feet or meters
- » Expanded capabilities with Optimo 2x and 1.4x range extenders

### Field of view for 35 mm Academic (22x16 mm)


Focal Length:	28 mm	76 mm	
Horizontal angular field of view:	42.8°	16.4°	
Object dimensions at MOD (mm):	345x246	126x92	



### Optimo Lightweight Lens + Optional Angénieux Servo Unit (ASU)



Angénieux Servo Unit provides control of zoom, focus and iris Optimo Lens + ASU = 2.65 kg / 5.8 lbs



Compatible with broadcast remote handles and cinema remote control



Extender 1.4x & Extender 2x



DSLR Mounts

### Optimo 45 - 120 Lightweight Series » Renowned Optimo quality in a lightweight lens Zoom Ratio: 2.7X with an incredible range Focal Length: 45 - 120 mm Aperture: f/2.6 - T2.8» Extremely fast aperture of T2.8 with MOD: 3 ft 1 in – 0.94 m no ramping Internal Focus: Yes

- »320° focus rotation with over 50 precise focus witness marks and minimal breathing
- » Unrivaled optical performance rivaling prime lenses at equivalent focal lengths
- » Available in PL mount. PV, Nikon, Canon mounts available upon request
- » Calibrated focus marks available in feet or meters (easily interchangeable focus ring)
- » Expanded capabilities with Optimo 2x and 1.4x range extenders

Image Coverage: S35+: 31.4mm diagonal

Weight (approx.): 4.3 lbs - 1.95 kg

Length: 203 mm Front Diameter: 114 mm

### Field of view for 35 mm Academic (22x16 mm)

Focal Length:	45 mm	120 mm	
Horizontal angular field of view:	27.4°	10.5°	
Object dimensions at MOD (mm):	415x298	154x113	



# Bring your content to life with true cinematic looks and 4k+quality

The proliferation of 4K digital screens and the advent of ultra definition television are escalating the demands for high quality motion picture content. A vast spectrum of new generation digital 35mm cameras has become available, and is being deployed in numerous production environments encompassing movies, dramas, commercials, concerts, and live sports events.

For over three quarters of a century, Angénieux has been serving the motion picture industry with zoom lenses of uncompromising quality, represented by the Optimo lens series. Optimo 24-290mm, 28-340mm and other Angénieux Cine lenses are already largely and commonly used for 4K concert and sport event shoots. The new Optimo Style family of zoom lenses inherits the virtues of the famed Optimo Cine lenses, with extra compatibility and production efficiency. All Optimo Style lenses are carefully manufactured to achieve a resolution of 4K and beyond, making them a sound investment for years to come. The Optimo Style family is initially comprised of two lightweight zoom lenses with an optional motorization system, and a 10x zoom lens inspired by the legendary Angénieux 25-250mm zoom.






### 16-40 Optimo Style Lightweight Lens + Optional Angénieux Servo Unit (ASU)



Angénieux Servo Unit provides control of zoom, focus and iris Optimo 16-40 Lens + ASU = 2.62 kg / 5.7 lbs



Compatible with broadcast remote handles and cinema remote control



Extender 1.4x & Extender 2x



DSLR Mounts



Wide Angle 0.75X

### Optimo Style 16 - 40 Lightweight Series » Extremely fast aperture of T2.8 with no Zoom Ratio: 2.5X ramping 16 - 40 mm Focal Length: »320° focus rotation with over 20 precise focus witness marks and no breathing f/2.6 - T2.8Aperture: 2 ft - 0.6 m MOD: Internal Focus: Yes » Optical design optimized for today's large format single sensor middle budget Image Coverage: S35+: 31.4 mm diagonal

» Calibrated focus marks in feet or meters

cameras with extended compatibility

- »Optimo quality and cinematic look at an affordable price
- » Available in PL mount. PV, Nikon and Canon mounts available on request
- » Expanded capabilities with Optimo 2x and 1.4x range extenders

Weight (approx.): 4.2 lbs - 1.92 kg

Length: 186 mm Front Diameter: 114 mm

### Field of view for 22x16 mm


Focal Length:	16 mm	40 mm	
Horizontal angular field of view:	69°	31.2°	
Object dimensions at MOD (mm):	569x408	230x170	



### Optimo Style Lightweight Lens + Optional Angénieux Servo Unit (ASU)



Angénieux Servo Unit provides control of zoom, focus and iris Optimo + ASU =  $2.62\ kg$  /  $5.7\ lbs$ 



Compatible with broadcast remote handles and cinema remote control



Extender 1.4x & Extender 2x



DSLR Mounts

## Optimo Style 30 - 76 Lightweight Series » Extremely fast aperture of T2.8 with no Zoom Ratio: 2.5X ramping Focal Length: 30 - 76 mm f/2.6 - T2.8Aperture:

»320° focus rotation with over 20 precise focus witness marks and no breathing

- » Optical design optimized for today's large format single sensor middle budget cameras with extended compatibility
- » Calibrated focus marks in feet or meters
- » Optimo quality and cinematic look at an affordable price
- » Available in PL mount. PV, Nikon and Canon mounts available on request
- » Expanded capabilities with Optimo 2x and 1.4x range extenders

MOD: 2 ft - 0.6 m

Internal Focus: Yes

Image Coverage: S35+: 31.4 mm diagonal

Weight (approx.): 4.2 lbs - 1.92 kg

Length: 186 mm Front Diameter: 114 mm

### Field of view for 22x16 mm

Focal Length:	30 mm	76 mm	
Horizontal angular field of view:	40.2°	16.4°	
Object dimensions at MOD (mm):	321x232	126x92	







Extender 1.4x & Extender 2x



DSLR Mounts

# Optimo Style 25 - 250

- » Low chromatic aberration, telecentricity and low distortion, ideal for high performance S35 digital cameras
- » Optimo quality and cinematic look at an affordable price
- » Optical design optimized for today's large format single sensor middle budget cameras with extended compatibility
- » Internal focus with minimal breathing
- » Image circle of 31.4 mm diagonal for perfect illumination of the S35 sensors
- » Very robust and precise zoom and focus mechanics with Angénieux unique rod guiding system design
- » Precise focus marks with easily interchangeable focus scale ring from feet to meters
- » Integrated filter holder for standard screw in filters
- » Optional front protective glass
- » Designed for easy maintenance
- » /£ Technology metadata interface\*
- » Standard PL mount lens. Panavision, Canon EF or Nikon F mounts optional

Zoom Ratio: 10X

Focal Length: 25 - 250 mm

**Aperture:** f3.2 – T3.5 with no ramping

**MOD:** 4 ft – 1.22 m

Internal Focus: Yes

Image Coverage: S35+: 31.4 mm diagonal


Weight (approx.): 16 lbs - 7.3 kg

**Length:** 377.4 mm **Front Diameter:** 136 mm

### Field of view for 22x16 mm

Focal Length:	25 mm	250 mm
Horizontal angular field of view:	47.6°	5°
Object dimensions at MOD (mm):	789x565	78.9x58.1

<sup>\*/\</sup>mathbb{B}\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right



# Optimo OP 30 ready package Stereoscopic production requires optical precision that is significantly more reading than that required in a 30 production. The Optime 30 ready

Stereoscopic production requires optical precision that is significantly more demanding than that required in a 2D production. The Optimo 3D ready lenses were designed and calibrated to meet and exceed these performance standards. Optimo 3D ready lenses are factory optimized with features like easily adjustable tracking, harmonized focus marks between the two lenses and like optical qualities, all to help acquire significantly improved 3D picture quality. 3D productions further benefit from flexibility of a compact, lightweight zoom lens and its ability to instantly and precisely change focal length without the need of dismantling a rig for frequent lens swaps.

- » similar "matched" optical quality
- » easily adjustable tracking
- »harmonized focus and zoom marks
- » customized travel case
- » available in 16-42 mm or 30-80 mm









# Optimo anamorphic lenses for Cinema Scope production with true aspect ratio

Angénieux's line of anamorphic zoom lenses enhances technique and creativity by giving film-like, dimensional character to images. Their unique optical design combining spherical and cylindrical elements in the same group delivers exceptional sharpness and lower distortion compared to typical anamorphic lenses. With two compact zoom models to meet all your anamorphic needs, you can bring more freedom of movement into the creative process with superior results, both in hand-held mode and on a Steadicam.

Based on the optical design of the 2012 SOC and 2009 Academy of Motion Picture award winning Optimo 28-76mm zoom lens, the 56-152mm 2S and the soon to be introduced 30-72mm 2S zoom lenses deliver exceptional optical performance never before seen with an anamorphic zoom.





# Optimo Anamorphic 56 - 152 2S Series 2.7X » Renowned Optimo quality in anamorphic Zoom Ratio: Focal Length: 56 - 152 mm » Anamorphic zoom with 2x squeeze f/3.6 - T4Aperture: » Fast aperture of T4 with no ramping MOD: 2 ft 1 in – 0.63 m »320° focus rotation with over 50 focus marks and no Internal Focus: Yes breathing Image Coverage: 4 perf. scope+: 28.8 mm diagonal »Superior optical performance with image flatness and low distortion

Weight (approx.): 4.8 lbs – 2.2 kg Length: 210 mm

**Length:** 210 mm **Front Diameter:** 114 mm

# Field of view for 35 mm 4 perf. (22x18.6 mm)

interchangeable focus scale ring)

» Available with PL mount. PV mounts available on request

» Calibrated focus marks available in feet or meters (easily

Focal Length:	56 mm	152 mm	
Horizontal angular field of view:	42.8°	16.4°	
Vertical angular of view:	18.7°	7.1°	



# Customer Service

# Quality

Each step of our service process is subject to rigorous controls under Thales Angénieux's ISO 9001 quality certification.

# Skill

Every repair benefits from the incomparable expertise of our technicians. Their experience, along with their proficiency in utilizing the most current specialized technologies to analyze and calibrate our premium optics, ensures the best possible outcome for our customers.

# Speed

For us it is a point of honor to serve our customers as swiftly as possible.

# Convenience

Our elite, highly trained international network of professional partners ensures your service needs can be managed locally and with the highest quality. Keep track of your service status easily and conveniently on our website. Individual serial numbers assigned to each Angénieux lens enable provenance to be maintained throughout the life of the lens.

See our service partner list on pages 46-47.

# Price

We use only the highest quality parts and take the time required to provide the most comprehensive and rigorous repairs possible. We also strive to provide you with the most economical repair achievable within those parameters. In addition, your service estimate, written after a full examination of your lens at the Angénieux factory, is always detailed and personalized.



# In their own words: industry professionals praise Optimo lenses

"...The two zooms (15-40 and 28-76) covered the whole range of focuses we needed. Most of the shots were done in a 28-40 mm range and often at 32 mm. So we simply inter-changed the two zooms. The longest focus we disposed of was 76 mm. We had to do two shots at 20 mm, that's all. With the sensitivity of today's digital cameras, T2.6 aperture is no longer a problem. Even on a boat, at 800 asa, it's very good..."

# - Guillaume Schiffman, Cinematographer, AFC

Feature film En Solitaire / Turning Tide by Christophe Offenstein

"...I used the 24-290 Optimo as soon as it came out, as it exactly matched my need in term of quality of skins and in colorimetry. It was for me the ideal lens. I also found these qualities, of course, with the 28-340, as well as with the lightweight Optimo 15-40 & 28-76. I could switch from a fixed camera with long focal to a shoulder camera with harmony. My shooting method is really focused on that. I usually mix with Cooke S4 and it works very well because I find the same quality..."

# - Jean-Marie Dreujou, Cinematographer, AFC

Feature film Le Totem du Loup / Wolf Totem by Jean-Jacques Annaud

"...I have been using Angénieux HR Zoom since my student days at FTII Pune. They have excellent definition, contrast and the colour rendering is neutral. Optimo 24-290 is a great lens. I have used them in a couple of feature films that I have shot. Optimo's power is more and with an aperture opening of 2.8 coupled with high speed film stock and today's digital cameras, it's very easy to shoot night sequences in available light. It's optical performance can be compared to prime lenses..."

# - Kiran Deohans, Cinematographer

Feature film Agneepath by Karan Malhotra

"...The scenes inside the bordello, the "Golden Pavilion," were often shot with the zoom, with Gong Her's father, and also the exterior day scenes. Kar Wai likes shooting with the zoom to give the character a certain depth. It's very hard to explain all the nuances, but the sense of a sequence can sometimes be reinforced through the use of the zoom. It becomes a narrative element in the writing..."

# - Philippe Le Sourd, Cinematographer

Feature film The Grandmaster by Wong Kar Wai

"...Visually, the colorimetry is the remarkable characteristic of this zoom. It faithfully reproduced the nuances of tone that are there in reality. Mechanically, it's exceptional – in situations where you change focus suddenly, the lens never "breathes." And obviously its lower weight and bulkiness differentiate it from other anamorphic zooms, which gives it great versatility..."

# - Gustavo Biazzi, Cinematographer

Feature film le Ciel du Centaure by Hugo Santiago – shot entirely with the Anamorphic Optimo 56-152 2S

"...It's clear that with the increasing number of requests for 4K TV productions, it is not only the question of having a camera with a better resolution. It is essential that all elements are at the same level. We can even say that the lens becomes more important than the camera. That's the point where we clearly see the advantage of the cine lenses..."

# - Ronald Meyvisch, New Technology Officer

From Euro Media Group on 4K Live Record-of-BNP Paribas Tennis Masters in Bercy (Paris)

"Gyro-Stabilized Systems develops leading-edge aerial camera systems like the C520 and C516 and our customers require the best lenses available for production work. The Angénieux Optimo line of lenses are considered the highest quality lenses by many aerial cinematographers worldwide, so it was a simple choice to ensure our gimbal designs were capable of integrating their lenses. The Angénieux team understand our specific business needs at GSS and have delivered on their promises each and every time."

# - Jason Fountaine, Managing Director

From GSS - Gyro-Stabilized Systems (Grass Valley - CA)

"...Both Optimos 24-290 and 15-40 proved themselves to be extremely versatile and productive during our day-to-day work. If in Joseph we had a set of fixed lenses plus the Optimos, in Pecado Mortal the Optimo lenses became our main lenses, specially in the studio scenes, as they allowed us to set the speed of shots that is required when shooting a tele-novela, which means 20 scenes per day in the studio. We basically used 8 Alexas with 6 Optimo 24-290 and 6 Optimo 15-40 plus a few fixed focal lenses. We used two studios with 3 cameras in each of them and two cameras for on-location shots. Optimo 24-290 were used inside the studio practically the whole time, while 15-40 and a fixed focal lens were chosen in more specific shots. On location, we used 15-40 most of the time together with a few fixed focal lenses..."

# - Alexandre Avancini, Director

The TV Series Pecado Mortal / Mortal Sin by Alexandre Avancini

"For a few years now, I've been incorporating organic motivated zooms into all my work. I find that the use of the zoom makes shots feel more immediate and intense. I dreamed for a long time of the perfect set of zooms. I was looking for zooms that could satisfy my desire for superior optics, optimum range, ergonomics and overall functionality. When the news of the Angénieux lightweight zooms was released, I was excited to work with them. They are truly amazing and totally satisfy everything I've been looking for in a set of lenses. I currently outfit each of my cameras with a full set of all three focal ranges and have been thrilled with the results."

# - Lisa Wiegand, Cinematographer

The TV Series Chicago Fire

read full testimonial on www.Angénieux.com

# TECHNICAL SPECIFICATIONS

35 mm Film and Digital CINEN	1A									
	Lens type	Optimo 15 - 40	NEW! Optimo 15 - 40 + ASU	Optimo 28 - 76	NEW! Optimo 28 - 76 + ASU	Optimo 45 - 120	NEW! Optimo 45 - 120 + ASU	Optimo 19.5 - 94	Optimo 24 - 290	Optimo 28 - 340
Zoom ratio		2.7x	2.7x	2.7x	2.7x	2.7x	2.7x	4.7x	12x	12x
Focal length min	mm	15	15	28	28	45	45	19.5	24	28
Focal length max	mm	40	40	76	76	120	120	94	290	340
Aperture		f/2.4 - T2.6	f/2.4 - T2.6	f/2.4 - T2.6	f/2.4 - T2.6	f/2.6 - T2.8	f/2.6 - T2.8	f/2.4 -T2.6	f/2.5 - T2.8	f/2.9 - T3.2
MOD	Meters	0.6	0.6	0.6	0.6	0.94	0.94	0.62	1.22	1.23
MOD	Feet	2'	2'	2'	2'	3' 1"	3' 1"	2' 0.5"	4'	4' 0.5"
	Format	S35+	S35+	S35+	S35+	S35+	S35+	S35+	35(1)	S35+
Image coverage	mm	31.4	31.4	31.4	31.4	31.4	31.4	31.4	30(1)	31.4
Sensor size	mm		For 35 mm Academic - 22x16 mm							
Horizontal angular FOV at focal min	Degrees	73°	73°	42.8°	42.8°	27.4°	27.4°	58.2°	49.2°	42.7°
Horizontal angular FOV at focal max	Degrees	31.2°	31.2°	16.4°	16.4°	10.5°	10.5°	13.4°	4.2°	3.8°
FOV at MOD at focal min	mm	611x437	611x437	345x246	345x246	415x298	415x298	344x246	799x571	687x493
FOV at MOD at focal max	mm	230x169	230x169	126x92	126x92	154x113	154x113	73x54	67x49	58x42
Front diameter	mm	114	114	114	114	114	114	136	162	162
Length	mm	186	186	186	186	203	203	335 / 330	440	454 / 449
Mount		PL(*)	PL(*)	PL(*)	PL(*)	PL(*)	PL(*)	PL / PV	PL(*)	PL / PV
Wainhi	kg	1.92 kg	2.62 kg	1.92 kg	2.62 kg	1.95 kg	2.65 kg	5.6 kg	11 kg	11.1 kg
Weight	lbs	4.2 lbs	5.7 lbs	4.2 lbs	5.7 lbs	4.3 lbs	5.8 lbs	12.3 lbs	24.2 lbs	24.4 lbs
		Accessories								
EXtender – 2x	EX 2x	yes	yes	yes	yes	yes	yes	yes	yes (with or without iris ring)	yes
EXtender – 1.4x	EX 1.4x	yes	yes	yes	yes	yes	yes	yes	yes (with or without iris ring)	yes
Nikon Mount (**)		yes	yes	yes	yes	yes	yes	no	-	no
Canon Mount (**)		yes	yes	yes	yes	yes	yes	no	yes	no
WA 0.75x (***)		yes	yes	no	no	no	no	no	no	no

<sup>(1)</sup> With 1.4x extender, image coverage becomes S35+: 31.4 mm diagonal (EPIC)

<sup>(\*)</sup> Panavision mount available at partner companies / Canon mount for Optimo 24-290, Optimo Style 25-250 & Lightweight are all different

<sup>(\*\*)</sup> Designed to replace the PL mount and allow Optimo (except 17-80) and Optimo Style to be used on DSLR cameras (APS-C format)

<sup>(\*\*\*)</sup> At wide angle only: focal length 15mm becomes 11.4mm, focal length 16mm becomes 12.2mm

# TECHNICAL SPECIFICATIONS

35 mm Film and Digital CINEMA		
	Lens type	
Zoom ratio		
Focal length min	mm	
Focal length max	mm	
Aperture		
MOD	Meters	
	Feet	
Image coverage	Format	
inago oovorago	mm	
Sensor size	mm	
Horizontal angular FOV at focal min	Degrees	
Horizontal angular FOV at focal max	Degrees	
FOV at MOD at focal min	mm	
FOV at MOD at focal max	mm	
Front diameter	mm	
Length	mm	
Mount		
Weight	kg	
	lbs	
EXtender 2x	EX 2x	
EXtender 1.4x	EX 1.4x	
Nikon Mount (**)		
Canon Mount (**)		
WA 0.75x (***)		

NEW! Optimo Style 16 - 40	NEW! Optimo Style 16 - 40 + ASU	NEW! Optimo Style 30 - 76	NEW! Optimo Style 30 - 76 + ASU	NEW! Optimo Style 25 - 250
2.5x	2.5x	2.5x	2.5x	10x
16	16	30	30	25
40	40	76	76	250
f/2.6 - T2.8	f/2.6 - T2.8	f/2.6 - T2.8	f/2.6 - T2.8	f/3.2 - T3.5
0.6	0.6	0.6	0.6	1.22
2'	2'	2'	2'	4'
S35+	S35+	S35+	S35+	S35+
31.4	31.4	31.4	31.4	31.4
		22x16 mm		
69°	69°	40.2°	40.2°	47.6°
31.2°	31.2°	16.4°	16.4°	5°
569x408	569x408	321x232	321x232	789x565
230x170	230x170	126x92	126x92	78.9x58.1
114	114	114	114	136
186	186	186	186	377.4
PL	PL	PL	PL	PL / PV
1.92 kg	2.62 kg	1.92 kg	2.62 kg	7.3 kg
4.2 lbs	5.7 lbs	4.2 lbs	5.7 lbs	16 lbs
yes	yes	yes	yes	yes
yes	yes	yes	yes	yes
yes	yes	yes	yes	-
yes	yes	yes	yes	yes
yes	yes	no	no	no

Optimo Anamorphic 56 - 152 2S
2.7x
56
152
f/3.6 - T4
0.63
2' 1"
4 perf. scope+
28.8
22x18.6 mm
42.8°
16.4°
344x143
126x54
114
210
PL / PV
2.2 kg
4.8 lbs
-
-
no
no
no

Optimo



<sup>(1)</sup> With 1.4x extender, image coverage becomes S35+: 31.4 mm diagonal (EPIC)

<sup>(\*)</sup> Panavision mount available at partner companies / Canon mount for Optimo 24-290, Optimo Style 25-250 & Lightweight are all different

<sup>(\*\*)</sup> Designed to replace the PL mount and allow Optimo (except 17-80) and Optimo Style to be used on DSLR cameras (APS-C format)

<sup>(\*\*\*)</sup> At wide angle only: focal length 15mm becomes 11.4mm, focal length 16mm becomes 12.2mm

# Angénieux Worldwide Partners

#### **AFRICA**

#### MOROCCO

LTS MAROC SALES

6 rue des hôpitaux 20 360 Casablanca Tel: + 212 (0)522 204 447 Fax: + 212 (0)522 204 470 Email: ali@lts-network.com

Email: jean@lts-network.com Web: www.shop.lts-network.com

#### **NIGERIA**

#### KONTAKT PRO NIGERIA SALES

Lagos & Abuja, Nigeria Tel: + 234 80 5222 8888 Email: sales@kontaktnigeria.com Web: www.kontaktnig.com

## **SOUTH AFRICA** MOVIE MART SALES

Film City Boulevard – Corner of N2 Highway & Baden Powell Drive Faure

Cape Town 7131

Email: philip@moviemart.co.za Web: www.moviemart.co.za

# **TUNISIA**

**SOGER** SALES 35 Rue du 1er Juin

Belvedere **1002 TUNIS** Tel: + 216 71 790 922

Fax: + 216 71 781 789 Email: soger.com@soger.com.tn

#### **AMERICAS**

#### **ARGENTINA**

FDM BROADCAST SRL SALES

Pavon 3521 Capital Federal

C1253 AAG BUENOS AIRES Tel: + 54 11 4921 9500 Fax: +54 11 4925 3000

Email: demarco@fdmbroadcast.com

## **BRAZIL EUROBRAS** SALES

Av. Graca Aranha 19 - GR.202

20030-002 RIO DE JANEIRO Tel: + 55 21 2240 3399 Fax: +55 21 2240 6430

Email: eurobras@eurobrastv.com.br

# **MEXICO**

CINETEC SA SALES

Protasio Tagle N° 79-A Col. San Miguel Chapultepec 11850 MEXICO DF

Tel: + 52 55 5516 0084 Fax: + 52 55 5273 0221 Email: curd@cinetec.com.mx Email: gunther@cinetec.com.mx Web: www.cinetec.com.mx

# **VENEZUELA**

**CINEMATERIALES CA SALES & SERVICE** Av A. Jahn. Entre 3ra v4ta

Transv. Calle Finca, Ota Santa Lucia Los Palos Grandes

1702 CARACAS Tel: + 58 2284 4144 Fax: +58 2284 4610

Fmail: edscheuren@cinematusa.com

#### **USA**

THALES COMPONENTS CO ANGÉNIEUX DIVISION (USA) **SALES & SERVICE** 

**40G Commerce Way** Totowa, NJ 07512-0540 Tel: + 1-973-812-3858 Fax: +1-973-812-9049 Sales: eparyzka@tccus.com Service: jbouchut@tccus.com

# ABELCINE BURBANK **SALES & SERVICE**

801 South Main St. Burbank, CA 91506 Tel: + 1-888-700-4416

Tel: + 1-818-972-9078 Fax: +1-818-972-2673 Email: orders@abelcine.com Web: www.abelcine.com

# ABELCINE NEW YORK **SALES & SERVICE**

609 Greenwich Street New York, NY 10014 Tel: + 1-888-223-1599

Tel: + 1-212-462-0100 Fax: +1-212-462-0199 Web: www.abelcine.com

#### **BANDPRO FILM & DIGITAL** SALES

3403 West Pacific Ave Burbank, CA 91505 Tel: + 1-818-841-9655 Fax: + 1-818-841-7649 Web: www.bandpro.com

# DUCLOS LENSES **SALES & SERVICE**

20222 Bahama Street Chatsworth, CA 91311

Tel: + 1-818-773-0600 Email: info@ducloslenses.com Web: www.ducloslenses.com

# E.N.G. OPTICAL SERVICES, INC SERVICE

1811 E. 1100 N. Road Milford II 60953

Tel: + 1-888-907-2836 Fax: + 1-815-889-4264 Email: engoptical@springmail.com

# HOT ROD CAMERAS SALES

1413 Cole Place Hollywood, CA 90028 Tel: +1 323.230.3589 Fax: +1 323.466.3589

Email: email@hotrodcameras.com Web: www.hotrodcameras.com

# TCS-TECHNOLOGICAL **CINEVIDEO SERVICES** SERVICE

341 West 38 Street 4th Floor New York, NY 10018

Tel: + 1-212-247-6517 Fax: +1-212-489-4886 Email: service@tcsfilm.com Web: www.tcsfilm.com

#### WEST COAST CINE VIDEO, INC. SALES

5739 Kanan Road, #307 Agoura Hills, CA 91301 Tel: + 1-818-742-8090

Email: sales@westcoastcinevideo.com Web: www.westcoastcinevideo.com

# **ASIA / PACIFIC**

# **AUSTRALIA**

**CINE AUSTRALASIA SALES & SERVICE** H74, 63-85 Turner Street PORT MELBOURNE VIC 3207 Tel: + 613 9646 6646 Fax: + 613 9646 6648

Email: cine aust@cine-equipment.com Web: www.cine-equipment.com

# **CHINA**

#### INFRATRANS VISION CHINA CO LTD SALES

Room 803 Tower B No. 7 Beitucheng Xilu Chaoyang District Beijing China 100029 Tel: + 86 10 8227 5579 Fax: +86 10 6480 2969 Email: info@itvc-cn.com Web: www.itvc-cn.com

# JEBSEN INDUSTRIAL TECHNOLOGY COMPANY LTD

SALES & SERVICE 28 Yun Ping Road 28F Lee Gardens II Hong Kong

Tel: + 852 29 238 774 Tel: + 852 29 262 337 Fax: +852 28 822 017 Email: junefung@jebsen.com Email: willyoon@jebsen.com Web: www.iebsenindustrial.com

# • SALES: PRODUCTS, PARTS AND ASSISTANCE • SERVICE: PARTS AND REPAIRS

# JEBSEN INDUSTRIAL (CHINA)

COMPANY LTD SALES

19F Fast Ocean Centre 618 Yan An Road East 200001 SHANGAI Tel: +86 21 23064774 Fax: +86 21 23064899 Email: emilyli@iebsen.com Web: www.jebsenindustrial.com

## JEBSEN INDUSTRIAL (CHINA) COMPANY LTD

SALES

28/F, Tower B, China International Center No.33 Zhongshan San Road Guangzhou 510055, P.R. China Tel: + 86 20 8713 7122 Fax: + 86 20 8713 7199 Email: eddyzheng@jebsen.com

#### JEBSEN INDUSTRIAL (CHINA) **COMPANY LTD**

**SALES & SERVICE** 10th Floor, Tower 2 Henderson Center No.18 JianGuoMenNei Dajie 100005 BEIJING

Tel: + 86 10 85198552 Fax: +86 10 85198699 Email: crystalli@jebsen.com Web: www.iebsenindustrial.com

#### **JAPAN**

# NAC IMAGE TECHNOLOGY INC. SALES & SERVICE

Aoyama Plaza Building 2-11-3 Kita-Aoyama Minato-Ku

Tokyo 107-0061 Tel: +81(0)3 3796 7903 Fax: +81(0)3 3796 7908

Fmail: masuda@camnac.co.in Web: www.nacinc.jp

# **MALAYSIA**

## CINE EQUIPMENT SDN. BHD SALES

No 177, Jalan Lancang Taman Seri Bahtera, Cheras 56100 KUALA LUMPUR Tel: +603 91331153 Tel: + 603 91335720 Fax: +603 91326351

Email: cine kl@cine-equipment.com Web: www.cine-equipment.com

# **NEW ZEALAND**

**PROTEL** SALES

15 Walter Street - PO Box 1073 6015 Wellington

Tel: + 64 4 801 9494 Fax: +64 4 384 2112 Email: ken.brooke@protel.co.nz Web: www.protel.co.nz

#### **PHILIPPINES**

# CINE EQUIPMENT PHILS INC

SALES 2/F Semicon Bldg #50 Marcos Highway Ngy. Dela Paz Pasig City Philippines 1611

Tel: + 632 249 1688 Fax: +632 249 1689 Email: cine ph@cine-equipment.com Web: www.cine-equipment.com

# **SINGAPORE**

# CINE EQUIPMENT PTE LTD **SALES & SERVICE**

10C Jalan Ampas. # 08-02 Ho Seng Lee Flatted Warehouse SINGAPORE 32 95 13

Tel: +65 6 252 50 89 Fax: +6562551981

Email: cine\_sin@cine-equipment.com Web: www.cine-equipment.com

#### **SOUTH KOREA**

SAMA GLOBAL VIDEO COMMUNICATIONS INC **SALES & SERVICE** 

6 P/L Dongguk Matrian Bldg. 84-2 Youngdeungpo-qu 150-836 SEOUL

Tel: +82 (2) 2636 1300 Fax: +82(2)26360040 Email: sales@samagvc.com Email: innk@samaqvc.com Web: www.samakorea.com

# TAIWAN

# CINE EQUIPMENT CO., LTD

SALES

8F., No.107, Lide St., Zhonghe Dist., New Taipei City 235, Taiwan (R.O.C.) Tel: + 886 - 2 - 3234 1234 Fax: +886 - 2 - 3234 1010 Director: Siew Moi Tng Email: smoitng@singnet.com.sg General Manager: Jack Chen Email: iack@cine-equipment.com

# **VIEW POINT IMAGE ASSEMBLINGS** SALES

Room A 11F N°251, Sec.2 HSIN-YI RD

TAIPEI 100 Tel: + 88 62 3393 0855 Fax: +88 62 3393 2828

Email: info.vpia@msa.hinet.net **THAILAND** 

# CINE EQUIPMENT CO LTD

SALES 580/15 Soi Ram Kham Haeng 39 (Soi Sahakarn-Pramoon) Pracha U-thit Road Wangthonglang 10310 BANGKOK Tel: +66 2 936 6557

Fax: +6629356044 Email:

cine thai@cine-equipment.com Web: www.cine-equipment.com

# **EURASIA**

# RUSSIA

SINTEX SALES

Ugreshskaya Street, 14 115088 Moscow Tel: + 7.495.679.81.71 Fax: +7.495.677.38.89 Email: karpov@sintex.ru Web: www.sintex.ru

#### SERNIA-FILM CO LTD SALES

Pvrieva Street 2 119285 Moscow

Tel: +7 499 143 23 23 Fax: +7 499 143 00 80 Email: ab@sernia-film.ru Email: be@sernia-film.ru Web: www.sernia-film.tv

# BARS-PRO SERVICE

Rublevskoe shosse 16 bld 4 121615 Moscow Tel: +7 495 415 98 13 Email: mail@bars-pro.ru Web: www.bars-pro.ru

# UKRAINE

#### **ENGINEER SERVICE** SALES

15 Vavylovykh str. Kiev, 04060

Tel: +380 (44) 593 18 20 Fax: ++380 (44) 593 18 20 Email: info@iservice.kiev.ua Web: www.serv.com.ua

# LATVIA

# HANNU PRO RIGA

SALES 11 Kugu Str., Riga, LV-1048, Latvia (3rd floor)

Tel: +371 67452206 Tel: +371 67452203 (pro solutions)

# Fax: +371 67624938 Email: mail@hannu-pro.com

# LITHUANIA HANNU PRO VILNIUS

SALES

Seimyniskiu Str. 1A. LT-09312 Vilnius. Lithuania

Tel: +370 52482565 Tel: +370 68633799 Fax: +370 52482565

Email: vilnius@hannu-pro.com

# **ESTONIA**

#### HANNU PRO TALLINN SALES

Tartu mnt 63, 10115, Tallinn, Estonia

Tel: +372 6155290 Tel: +372 5088511 Fax: +372 6155291

Email: tallinn@hannu-pro.com

# **EUROPE**

#### **AUSTRIA**

LB ELECTRONICS GMBH SALES

Doblinger Hauptstrasse 95

1190 WIEN Tel: +43 1 360 30 Fax: +43 1 369 84 43

Email: video@lbe.co.at WEB: www.lb-electronics.at

### **BELGIUM**

**VP MEDIA SOLUTIONS** SALES

3 place Thomas Balisplein 1160 BRUSSELS Tel: + 32 2 640 39 94 Fax: + 32 2 640 02 41

Email: info@vpmediasolutions.com Web: www.vpmediasolutions.com

#### **BOSNIA AND HERZEGOVINA**

ROBERT'S PLUS D.O.O. SALES

Marka Marulica 2/V 71000 SARAJEVO Tel: + 387 33 640 818

Fax: + 387 33 640 818 Email: robertsplus@robertsplus.ba Web: www.robertsplus.hr

#### **BULGARIA**

TECHNO BULGARIA SALES

Vrajdebna District, 32 Str., No. 6 BG-1839 Sofia

Tel: + 359 2 946 0786 Fax: +359 2 946 3503 Email: sales@techno.bg Email: peter.petrov@techno.bg Web: www.technostore.bg

#### CROATIA

ROBERT'S PLUS D.O.O.

SALES Marasoviceva 67

21000 SPLIT Tel: + 385 21 315 800

Fax: + 385 21 315 804 Email: robertsplus@robertsplus.hr

Web: www.robertsplus.hr

#### **CZECH REPUBLIC** SYNTEX PRAHA

SALES

Address 1: Michelska 21 14000 Prague

Address 2: MichelskÃi 21 14100 Praha 4 - Michle Tel: + 420 241 482 662 Email: info@svntex.cz Web: www.syntex.cz

AVD SYSTEMS S.R.O. SALES

Ceske druziny 18 16000 PRAHA 6

Tel: + 420 224 250 259 Fax: + 420 224 254 722 Email: avdinfo@avd.cz Web: www.avd.cz

#### **DENMARK**

**BICO PROFESSIONEL A/S SALES & SERVICE** Mose Alle 16 2610 RODOVRE

Tel: + 45 3584 0295 Fax: + 45 3584 0695 Email: mogens@bico.dk Web: www.bico.dk

# **FINLAND**

OY HEDCOM AB SALES

PO Box 110 Lauttasaarentie 50 00201 HELSINKI Tel: + 358 207 638 000

Fax: + 358 968 284 674

Email: pekka.junttonen@hedcom.fi Web: www.hedcom.fi

#### FRANCE

THALES ANGÉNIEUX SALES & SERVICE Bd Ravel de Malval 42570 SAINT-HEAND

Tel: + 33 (0)4 77 90 78 99 Fax: + 33 (0)4 77 90 78 03

cecile.bouchou@fr.thalesgroup.com Web: www.angenieux.com

# **GERMANY**

BEBOB GMBH SALES

Höglwörther Str. 350 D-81379 MUNICH Tel: + 49 89 2781 8282 Fax: + 49 89 2781 8281 Email: pierre.boudard@bebob.de

**GREECE** CALAVITIS S.A. SALES

Antinoros 11,11634, Athens, Greece Tel: +210 7248144

Fax: +210 7291613 Email: info@calavitis.gr Web: www.calavitis.gr

Web: www.bebob.de

#### HUNGARY

REXFILM BROADCAST & COMMUNICATONS SYSTEMS LTD SALES

Etele Ut 59-61 1119 BUDAPEST Tel: + 36 1 283 7160 Fax: + 36 1 283 7166 Email: BelaSztupa@rexfilm.hu

## SOMOS BROADCAST MEDIA ZRT SALES H-1141 Budapest, Liptovar u.2

Tel: + 36 1 460 8047 Fax: + 36 1 460 8051 Email: judy@sbmzrt.hu Web: www.sbmzrt.hu

# ITALY

CARTONI S.P.A.

SALES Via Giuseppe Mirri 13 00159 ROMA

Tel: + 39 064 38 20 02 Fax: + 39 064 35 88 293 Email: cartoni@cartoni.com Web: www.cartoni.com

#### PANATRONICS SRL SALES

Via Maderna 8 20138 MILANO

Tel: + 39 025 51 95 561 Fax: + 39 025 51 95 658 Fmail

commerciale@panatronics.com Web: www.panatronics.com

# NORWAY VIDEO 4

SALES

Sandbrekkevegen 100 / 5225 Nesttun -Bergen

Tel: +47 56 90 42 10 Fax: +47 56 90 42 11 Email: firma@video4.no Web: www.video4.no

# **POLAND** JBD SA

SALES

22/26 Tuwima Street 90-002 LODZ

Tel: + 48 42 630 6888 Fax: + 48 42 632 1767 Email: jbd@jbd.com.pl Email: piotr@ibd.com.pl Email: tomek@ibd.com.pl Web: www.jbd.com.pl

# **PORTUGAL**

VIDEOMATER SALES

Av de Padua, Nº 10H 1800-297 LISBOA Tel: + 35 1 218 549 113

Tel: + 35 1 912 567 979 Fax: + 35 1 218 549 112 Email: videomater@sapo.pt

# **ROMANIA** PBR LTD SALES

32 Corbeni Str. / District 2 020784 BUCHAREST

Tel: +40 21 316 9673 / 9674 Fax: +40 21 316 9733 Email: office@pbr.com.ro Web: www.pbrstore.ro

# **SERBIA & MONTENEGRO**

RTC SALES

Koste Glavinica 9 11030 Belgrade, Serbia Tel: + 381 (11) 3699224

Tel: + 381 (11) 3699916 Fax: +381 (11) 3699917 Email: office@rtc.rs Email: nina.rsumovic@rtc.rs Web: www.rtc.rs

# **SLOVAKIA**

SYNTEX BRATISLAVA S.R.O. SALES

Zeleznicna 23 82107 Bratislava Tel: + 421 2 4552 5471

Email: info@syntex.sk Web: www.syntex.sk

#### SPAIN

VIDEO CINE IMPORT SALES

Avda. Somosierra, 20, Nave 4 28703 San Sebastian de los Reves (MADRID)

Tel: + 34 916 63 64 66 Fax: + 34 916 53 60 30

Email: info@videocineimport.com Web: www.videocineimport.com

# **SWEDEN** CAMERA NORDIC SALES

Industrigatan 4 112 46 Stockholm Tel: + 46 8 410 462 40

Email: info@cameranordic.com Web: www.cameranordic.com

# SWITZERLAND (NORTHERN)

VIDEOLINK AG SALES

8800 THALWIL Tel: + 41 44 723 3880 Fax: + 41 44 723 3881

Email: info@videolink.ch Web: www.videolink.ch

### **VISUALS SWITZERLAND** SALES

8 rue du Pré-Bouvier 1217 Meyrin Tel: +41 22 561 07 07

Web: www.visuals-switzerland.net/fr/

# THE NETHERLANDS ANGÉNIEUX CARTANGE SALES

Brabantlaan 27 4902 BJ OOSTERHOUT Tel: + 31 16 24 60 700 Fax: + 31 16 24 33 911 Email: joop@vgorsel.nl Web: www.cartange.nl

# **TURKEY** KAPRO

SALES Kasap Ismail Sk. No:15/9. Sadikoglu Is Merkezi 4 34722 Hasanpasa, Kadıköv Istanbul

Tel: +90 216 700 1035 Email: info@kapro.com.tr Web: www.kapro.com.tr

# UK

# CVP LONDON

SALES 23-25 Shield Drive West Cross Industrial Estate Brentford Middlesex

TW8 9FX Tel: + 44 (0) 20 8380 7400 Fax: + 44 (0) 020 8380 7410 Email: sales@cvp.com

Web: www.creativevideo.co.uk CVP MIDLANDS

SALES Priory Mill Castle Road Studley Warwickshire B80 7AA

Tel: + 44 (0) 1527 854 222 Fax: +44(0) 1527 857 666 Email: sales@cvp.com Web: www.creativevideo.co.uk

#### MIDDLE EAST

IRAN

TELEKALA CO LTD **SALES** 

Enghelab Sq. Shahre Tamasha Building P.O. Box 13145 1314 TEHRAN

Tel: + 00 98 21 66 94 88 54 Fax: +00 98 21 66 43 35 85 Email: f kamrani@telekala.com

**ISRAEL** 

PROLOG OPTICS SALES

4 Ha Horesh Road P.O.B. 12193 Yehud 56470

Tel: + 972 3 536 4011 Fax: +972 3 536 4012 Email: tal@prologltd.com Web: www.prologoptics.com

# **UNITED ARAB EMIRATES & GCC** ADVANCED MEDIA TRADING LLC

SALES 4th floor, 410, Al Khaleej Centre, Bur Dubai, Dubai United Arab Emirates Tel: + 971 43529977

Fax: + 971 43529976 Email: info@amt.tv Web: www.amt.tv

# **UNITED ARAB EMIRATES**

AMARANTHINE SALES

P.O. Box 124137 Warehouse #37, Al Qouz Ind. Area 1. Road 8. Interchange 3. Sheikh Zayed Rd., Dubai Tel: +971 4 3390944

Fax: +971 4 3390922 Email: info@amaranthine.ae Web: www.amaranthine.tv

# **O**ngenieux<sup>®</sup>

Thales Angénieux Headquarters Boulevard Ravel de Malval 42570 Saint-Héand (France) Tel: +33 (0)4 77 90 78 00 Fax: +33 (0)4 77 90 78 03 angenieux@fr.thalesgroup.com

Thales Angénieux in the USA 40G Commerce Way Totowa, NJ 07512 Tel: 1 973 812 3858 Fax: 1 973 812 9049 angenieux@tccus.com

Thales Angénieux in Asia 10C Jalan Ampas #08-02 Ho Seng Lee Flatted Warehouse Singapore 329513 Tel: +65 63 56 81 98 Fax: +65 62 50 60 85 angenieux@fr.thalesgroup.com

Thales Angénieux in India 703-A&B, Tower C - 7th floor "Konnectus" Building Bhavbhuti Marg. New Delhi -110 001 India angenieux@fr.thalesgroup.com


# www.angenieux.com











# Photo copyrights:

(p.8) Wolf Totem / le Totem du Loup © China film Co., LTD / Repérage

(p.9 and 18) En Solitaire / Turning Tide © Riou

(p.9) © Anil Mehta

(p.9) Flies the Red Epic Dragon © gyro-Stabilized Systems, LLC

(p.9) Chicago Fire © Wolff films

(p.10) Un Heureux Evènement / A Happy Event © Nicolas Schul

(p.26) © United - Muse concert 4K Live record - Roma July 6th, 2013

(p.34) Le Ciel du Centaure / El Cielo del Centauro © Pierre Lazarus